



TN 127

- Raccordo di estremità a L
- L-Einschraubverschraubungen
- Stud Barrel Tees
- Té mâle renversé

Filettatura:
Gas conica
Metrica conica
NPT

Einschraubgewinde:
Withworth-Rohrgewinde kegelig
Metrisches Feingewinde kegelig
NPT

Thread:
B.S.P. tapered
Metric tapered
NPT

Filetage:
Gaz conique
Métrique conique
NPT

| Serie Reihe Series Série | Ø Tubo Rohr AD Tube O.D. Ø Tube d _t | PN | Ø F2 | | | a) | I | L | L1 | a) | L2 | CH1 | CH2 | Simbolo di ordinazione - Bestell-Nr. Part. No. - Références | | | Peso Gewicht Weight Poids kg. x100 P. |
|-----------------------------------|--|-----|--------|----------|--------|----|----|------|----|----|----|-----|-----------------|--|------------------|-------|---|
| | | | R | M | NPT | | | | | | | | | R | M | NPT | |
| | | | LL | 4 | 100 | | | | | | | | | 1/8" | 8 × 1 | 1/8" | |
| | 5 | | 1/8" | 8 × 1 | 1/8" | 8 | 21 | 9,5 | 17 | 12 | 9 | 12 | TN 127 - 5 LLR | TN 127 - 5 LLM | TN 127 - 5 LLNPT | 3,0 | |
| | 6 | | 1/8" | 10 × 1 | 1/8" | 8 | 21 | 9,5 | 17 | 12 | 9 | 12 | TN 127 - 6 LLR | TN 127 - 6 LLM | TN 127 - 6 LLNPT | 3,0 | |
| | 8 | | 1/8" | 10 × 1 | 1/8" | 8 | 23 | 11,5 | 20 | 14 | 12 | 14 | TN 127 - 8 LLR | TN 127 - 8 LLM | TN 127 - 8 LLNPT | 4,0 | |
| | 10 | | 1/4" | - | - | 12 | 27 | 15 | 25 | 17 | 14 | 17 | TN 127 - 10 LLR | - | - | 6,6 | |
| | 12 | | 1/4" | - | - | 12 | 25 | 13 | 23 | 19 | 17 | 19 | TN 127 - 12 LLR | - | - | 8,7 | |
| L | 6 | 315 | 1/8" | 10 × 1 | 1/8" | 8 | 27 | 12 | 20 | 14 | 12 | 12 | TN 127 - 6 LR | TN 127 - 6 LM | TN 127 - 6 LNPT | 5,5 | |
| | 8 | | 1/4" | 12 × 1,5 | 1/4" | 12 | 29 | 14 | 26 | 17 | 12 | 12 | TN 127 - 8 LR | TN 127 - 8 LM | TN 127 - 8 LNPT | 7,5 | |
| | 10 | | 1/4" | 14 × 1,5 | 1/4" | 12 | 30 | 15 | 27 | 19 | 14 | 14 | TN 127 - 10 LR | TN 127 - 10 LM | TN 127 - 10 LNPT | 11,0 | |
| | 12 | | 3/8" | 16 × 1,5 | 3/8" | 12 | 32 | 17 | 28 | 22 | 17 | 17 | TN 127 - 12 LR | TN 127 - 12 LM | TN 127 - 12 LNPT | 13,0 | |
| | 15 | | 1/2" | 18 × 1,5 | 1/2" | 14 | 36 | 21 | 34 | 27 | 19 | 19 | TN 127 - 15 LR | TN 127 - 15 LM | TN 127 - 15 LNPT | 22,0 | |
| | 18 | | 1/2" | 22 × 1,5 | 1/2" | 14 | 40 | 23,5 | 36 | 32 | 24 | 24 | TN 127 - 18 LR | TN 127 - 18 LM | TN 127 - 18 LNPT | 32,0 | |
| | 22 | 160 | 3/4" | - | 3/4" | 16 | 44 | 27,5 | 42 | 36 | 27 | 27 | TN 127 - 22 LR | - | TN 127 - 22 LNPT | 40,0 | |
| | 28 | | 1" | - | 1" | 18 | 47 | 30,5 | 48 | 41 | 36 | 36 | TN 127 - 28 LR | - | TN 127 - 28 LNPT | 56,0 | |
| | 35 | | 1" 1/4 | - | 1" 1/4 | 20 | 56 | 34,5 | 54 | 50 | 41 | 41 | TN 127 - 35 LR | - | TN 127 - 35 LNPT | 90,0 | |
| | 42 | | 1" 1/2 | - | 1" 1/2 | 22 | 63 | 40 | 61 | 60 | 50 | 50 | TN 127 - 42 LR | - | TN 127 - 42 LNPT | 135,0 | |
| S | 6 | 630 | 1/4" | 12 × 1,5 | 1/4" | 12 | 31 | 16 | 26 | 17 | 12 | 12 | TN 127 - 6 SR | TN 127 - 6 SM | TN 127 - 6 SNPT | 10,0 | |
| | 8 | | 1/4" | 14 × 1,5 | 1/4" | 12 | 32 | 17 | 27 | 19 | 14 | 14 | TN 127 - 8 SR | TN 127 - 8 SM | TN 127 - 8 SNPT | 12,0 | |
| | 10 | | 3/8" | 16 × 1,5 | 3/8" | 12 | 34 | 17,5 | 28 | 22 | 17 | 17 | TN 127 - 10 SR | TN 127 - 10 SM | TN 127 - 10 SNPT | 16,0 | |
| | 12 | | 3/8" | 18 × 1,5 | 3/8" | 12 | 38 | 21,5 | 31 | 24 | 17 | 17 | TN 127 - 12 SR | TN 127 - 12 SM | TN 127 - 12 SNPT | 20,0 | |
| | 14 | | 1/2" | 20 × 1,5 | 1/2" | 14 | 40 | 22 | 32 | 27 | 19 | 19 | TN 127 - 14 SR | TN 127 - 14 SM | TN 127 - 14 SNPT | 25,0 | |
| | 16 | 400 | 1/2" | 22 × 1,5 | 1/2" | 14 | 43 | 24,5 | 32 | 30 | 24 | 24 | TN 127 - 16 SR | TN 127 - 16 SM | TN 127 - 16 SNPT | 32,0 | |
| | 20 | | 3/4" | - | 3/4" | 16 | 48 | 26,5 | 42 | 36 | 27 | 27 | TN 127 - 20 SR | - | TN 127 - 20 SNPT | 48,0 | |
| | 25 | | 1" | - | 1" | 18 | 54 | 30 | 48 | 46 | 36 | 36 | TN 127 - 25 SR | - | TN 127 - 25 SNPT | 92,0 | |
| | 30 | | 1" 1/4 | - | 1" 1/4 | 20 | 62 | 35,5 | 54 | 50 | 41 | 41 | TN 127 - 30 SR | - | TN 127 - 30 SNPT | 130,0 | |
| | 38 | | 1" 1/2 | - | 1" 1/2 | 22 | 72 | 41 | 61 | 60 | 50 | 50 | TN 127 - 38 SR | - | TN 127 - 38 SNPT | 190,0 | |

- Le dimensioni di ingombro si intendono a raccordo chiuso.
- Baumaße sind ca.-Maße bei angezogener Überwurfmutter.

- Overall sizes are with closed fitting.
- Les dimensions d'encombrement s'entendent raccord monté.
- a) TN 127 - 15 LM L2 = 32
- TN 127 - 14 SNPT L2 = 34; I = 16
- TN 127 - 16 SNPT L2 = 36; I = 16

TN127 M-NTP DISPONIBILE FINO AD ESAURIMENTO - VERFÜGBAR NUR SOLANGE VORRÄTIG - AVAILABLE WHILE STOCKS LAST - DISPONIBLE JUSQU'A EPUISEMENT DE NOTRE STOCK