

Maschi a macchina "corti" ISO 529


Short machine taps ISO 529 / Tarauds machine courte ISO 529
Machos de maquina cortos ISO 529 / Kurzmaschinen-Gewindebohrer



10172 **10173**



ISO 529/B ISO 529/35°C



Applicazioni / Applications

R ≤ 850 N/mm²



Inox



Acciaio Steel



Metals



Art. 10172
HSS-G

M

	Ø	/	L	d	pcs	cod.	€ cad/each
M	3 x 0,5	11	48	3,15	1	1017203X05	
	4 x 0,7	13	53	4	1	1017204X07	
	5 x 0,8	16	58	5	1	1017205X08	
	6 x 1	19	66	6,3	1	1017206X1	
	8 x 1,25	22	72	8	1	1017208X125	
	10 x 1,5	24	80	10	1	1017210X15	
	12 x 1,75	29	89	9	1	1017212X175	



M 3÷12 7 pcs
10240313 HSS-G
€

Art. 10173
HSS-G

	Ø	/	L	d	pcs	cod.	€ cad/each
M	3 x 0,5	11	48	3,15	1	1017303X05	
	4 x 0,7	13	53	4	1	1017304X07	
	5 x 0,8	16	58	5	1	1017305X08	
	6 x 1	19	66	6,3	1	1017306X1	
	8 x 1,25	22	72	8	1	1017308X125	
	10 x 1,5	24	80	10	1	1017310X15	
	12 x 1,75	29	89	9	1	1017312X175	



M 3÷12 7 pcs
10240314 HSS-G
€


Punta-Maschio a macchina per forature e filettature in una sola operazione.

Combined machine drill-tap for drilling and threading in one operation / Foret taraudeur à machine, filetage métrique
Brocas-macho, rosca métrica normal / Maschinen-kombi-Gewindebohrer für metrisches ISO Regel-Gewinde

10290



DIN 357
ISO 2/6H



Art. 10290
HSS-CO

M

	Ø	L	d1	d2	pcs	cod.	€ cad/each
M	3 x 0,5	56	2,5	3	1	1029003X05	
	4 x 0,7	63	3,3	4	1	1029004X07	
	5 x 0,8	71	4,2	5	1	1029005X08	
	6 x 1	80	5	6	1	1029006X1	
	8 x 1,25	95	6,8	8	1	1029008X125	
	10 x 1,5	106	8,5	10	1	1029010X15	
	12 x 1,75	125	10,2	12	1	1029012X175	