



## MASCHI A MANO

## ■ Art. T325

MASCHI A MANO IN SERIE DI DUE PEZZI  
INDUSTRIAL QUALITY

**CARATTERISTICHE**  
Filettatura GAS cilindrica (R).  
DIN 353 - UNI 3805 - HSS G  
PROFILO RETTIFICATO

| ART.  | dimensioni |           |            |       |       |          |
|-------|------------|-----------|------------|-------|-------|----------|
|       | Ø mm       | n.fil./1" | Ø d1 H9 mm | L1 mm | L2 mm | a H11 mm |
| 1/8   |            | 28        | 7          | 63    | 18    | 5,5      |
| 1/4   |            | 19        | 11         | 63    | 20    | 9        |
| 3/8   |            | 19        | 7          | 12    | 70    | 9        |
| 1/2   |            | 14        | 16         | 80    | 22    | 12       |
| 5/8   |            | 14        | 18         | 90    | 25    | 14,5     |
| 3/4   |            | 14        | 20         | 100   | 28    | 16       |
| 7/8   |            | 14        | 22         | 100   | 28    | 18       |
| 1"    |            | 11        | 25         | 110   | 32    | 20       |
| 1-1/8 |            | 11        | 28         | 110   | 32    | 22       |
| 1-1/4 |            | 11        | 32         | 125   | 32    | 24       |
| 1-1/2 |            | 11        | 36         | 140   | 32    | 29       |
| 1-3/4 |            | 11        | 36         | 160   | 36    | 29       |
| 2"    |            | 11        | 36         | 160   | 36    | 29       |
| 2-1/4 |            | 11        | 40         | 160   | 36    | 32       |
| 2-1/2 |            | 11        | 45         | 160   | 36    | 35       |
| 2-3/4 |            | 11        | 50         | 160   | 40    | 39       |
| 3"    |            | 11        | 50         | 160   | 40    | 39       |

